



SIZE	$\varnothing AL$ (mm.)	Min. Bending radius (mm.)	Max. Working Pressure (Bar@20Deg.C)	Max. Working Temp. (Deg.C)	Lateral Movement (mm.)	H1 (mm.)	H2 (mm.)	(M) x 2 (mm.)	BSPT-THREAD
15A	300	200	16	250	62	37	27	74	1/2"
20A	300	200	16	250	62	44	33	74	3/4"
25A	300	200	16	250	55	53	41	86	1"
32A	300	250	16	250	41	62	50	94	1-1/4"
40A	300	250	16	250	40	72	56	99	1-1/2"
50A	300	350	16	250	25	86	69	110	2"

7	UNION END	FCMB	2
6	UNION NUT	FCMB	2
5	UNION GASKET	NON ASBESTOS	2
4	COLLAR	SS 400	2
3	LAP RING	SS 400	2
2	SPIRAL HOSE	SUS304	1
1	WIRE BRAID	SUS304	1
ITEM	PART NAME / DESCRIPTION	MATERIAL	Q'TY

PROPRIETARY DATA
THIS DOCUMENT CONTAINS TOZEN INDUSTRIAL CO.,LTD. CONFIDENTIAL INFORMATION AND SHOULD NOT BE USED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF TOZEN INDUSTRIAL CO.,LTD.

TOZEN INDUSTRIAL CO.,LTD.
3388/62 18th Fl. Sirinrat Bldg,
Rama IV Rd., Klongtoey,
Bangkok 10110

MANUFACTURING TOLERANCES (UNLESS SPECIFIED OTHERWISE) TOLERANCES TO BE NON-CUMULATIVE					TITLE: SF100 NW	
LINEAR			ANGULAR	ROUNDNESS (CIRCULARITY)	CYLINDRICITY	
0 - 50 mm (INCL) ± 0.2 mm	50 - 500 mm (INCL) ± 0.5 mm	OVER 500 mm (INCL) ± 1 mm	± 1°	± 0.5 mm	± 0.5%	
NAME	SIGNATURE	DATE				
DRAWN	MATERIAL:		DWG NO. -			
CHK'D			A4			
APPV'D			SHEET 1 OF 1			
MFG			SCALE:1:2			
Q.A			UNIT : mm			
			REVISION : 00			